M.L.A. INDUSTRIES

SORP. ADDRESS: 111/230, HARSH NAGAR, KANPUR — 208 012

Emm Ales@mlagroup.com

PH: 0512-3069261, 2255592, 2526257, 2545548

website: www.mlagroup.com











Manufacturers of Precipated Silica, HCS, Azodicarbonamide, Zinc, Calcium, Aluminum Stearate, Zinc Oxide (active) and PVC Stablizer

QUALITY ASSURANCE REPORT

CUSTOMER NAME

: R.K. POLYMER

INVOICE NO. : 55

PRODUCT

: PRECIPITATED SILICA

GRADE

: NK-70

TOTAL QUANTITY

: 1000

KG

DATE

: 08-Apr-2014

DOC NO.

2No PROPERTY	SPECIFICATION	UNIT	BATCH WISE TEST VALUE	
KOPKOI LKI I				<u>5D/4</u>
1 Moisture	5 + - 1.5	%		5.4
2 Bulk Density	0.12 - 0.16	gm/cc		0.15
3 pH Value	6.5 - 7.5			6.99
4 Water Absorption	230 - 260	%		250
5 Loss On Ignition	6.0 max	%		5.67
6 Residue on 300 Mesh	1.0 max	%		0.17
7 Colour	White powder			As per std

1) IR Moisture Balance (At the time of Packing) , 2) After 50 tappings , 3) By pH Meter , 5) At 1000 °C.

, 7) Visual Observation ,

REMARKS (IF ANY)

APPROVED OR REJECTED

APPROVED BY

^{*} The above test results are typical and indicative. This information and our technical advice whether verbal, in writing or by way of trials are given in good faith but without warranty. It does not release you from obligation to check its validity and to test our products as to thier suitability for the intended process and uses. The handling application, use and processing of our products in your formulation in the products manufactured by ou are beyond our control and, therefore entirely your own responsibility.



GMP

Right Chemistry - Right People

^{*} We do visual comparison of test sample with standard in powder form or acqueous slurry because it is the easiest and most reliable method for control colour / whiteness

^{*} Any difference on the above values must be brought to our notice with in 7 days of receipt of the consignment