KANPUR CHEMICAL INDUSTRIES

CORR. ADDRESS: 111/230, HARSH NAGAR, KANPUR — 208 012

Email-sales@mlagroup.com

PH: 0512-3069261, 2255592, 2526257, 2545548

website: www.mlagroup.com











Precipitated and Natural Aluminium and Calcium Silicate

QUALITY ASSURANCE REPORT

CUSTOMER NAME

: R.K. POLYMER

INVOICE NO.

45

PRODUCT

: CALCIUM SILICATE

GRADE

: 3STAR

TOTAL QUANTITY

: 2000

KG

DATE

: 20-Jul-2014

DOC NO.

.

SNoPROPERTY		SPECIFICATION	UNIT	BATCH WISE TEST VALUE	
				<u>25D/5</u> <u>16N/6</u>	13N/6
1	Moisture	2.0 max	%	1.10 1.00	1.05
2	Bulk Density	0.50 - 0.55	gm/cc	0.53 0.54	0.53
3	Water Absorption	38 - 42	%	41 40	41
4	pH Value	8.0 - 9.0		8.72 8.75	8.74
5	Residue on 500 mesh	2.5 max	%	1.13 1.15	1.13
6	Average Particle Size	6.0 - 8.0	μm	7.15 7.13	7.16
7	Colour	As per std	-	Conforme to Std Std	Conforme to std

1) IR Moisture Balance (At the time of Packing), 2) After 50 tappings, 4) By pH Meter, 5) Wet Seiving, 6) LPSD Analyser, 7) Visual Observation,

REMARKS (IF ANY)

APPROVED OR REJECTED

APPROVED BY

QC. OFFICER

- - Right People



^{*} We do visual comparison of test sample with standard in powder form or acqueous slurry because it is the easiest and most reliable method for control colour / whitenes.

^{*} Any difference on the above values must be brought to our notice with in 7 days of receipt of the consignment

^{*} The above test results are typical and indicative. This information and our technical advice whether verbal, in writing or by way of trials are given in good faith but without warranty. It does not release you from obligation to check its validity and to test our products as to thier for the intended process and uses. The handling application, use and processing of our products in your formulation in the